




























	Standard	Result	Product	Size (mm)
 Size		See separate table	RKP8101	1420 x 225
 Locking system*		5G® fold down installation system	RKP8103	1420 x 225
 Thickness	ISO 24346	6,5 mm	RKP8104	1420 x 225
 Wear layer	ISO 24340	0,55 mm	RKP8105	1420 x 225
 Surface treatment		K-Guard+ PU coating	RKP8107	1420 x 225
 Warranty	Commercial	15 years**	RKP8108	1420 x 225
	Residential	30 years**	RKP8109	1420 x 225
 Bevelled edge		Micro	RKP8111	1420 x 225
 Mass per unit area	ISO 23997	7480 g/m ²	RKP8112	1420 x 225
 Standards	EN 16511	Multilayer modular floorcovering panels	RKP8116	1420 x 225
 Classification	ISO 10874 Commercial	33:-Commercial heavy	RKP8117	1420 x 225
	ISO 10874 Domestic	23:-Domestic heavy	RKT2401	457 x 600
 Reaction to fire	EN13501-1	B _{fl} -s1	RKT2402	457 x 600
 Staining	EN 438-2	pass (grade 5)	RKT2404	457 x 600
 Light fastness	EN ISO 105-B02	pass ≥6	RKT2405	457 x 600
 Abrasion resistance	EN13329 Annex E	pass 4000 cycles	RKT2406	457 x 600
 Furniture chair leg	EN424	pass (no visible damage)		
 Dimensional stability	EN ISO 23999	pass ≤0,25%		
 Swelling	ISO 24336	pass (0,2 %)		
 Acoustic impact noise reduction	EN ISO 10140-1:2016 and EN ISO 10140-3:2010+A1:2015	ΔL _w = 21 dB ΔL _{LIN} = 11 dB		
 Indentation-residual	ISO 24343-1	Pass ≤ 0,1 mm		
 Impact resistance	EN13329 Annex F	pass ≥1800 mm		
 Castor chair continuous use	ISO 4918/EN425	pass 25 000 cycles		
 Thermal resistance	ISO 8302	0,052 m ² K/W suitable for underfloor heating max 27 °C		
 Slip resistance***	EN 13893 DIN 51130	DS R10		
 Environmental	Indoor Air Comfort French VOC regulation (ISO 16000) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)		
 Recycling		Suitable		
 Phthalate free		Yes		
 Adhesive	None required; please install according to our installation instructions.			

*5G® is a patented technology invented by Välinge Innovation AB. The 5G® word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

**Subject to terms see website

***Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132

Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386

e: info@designflooring.com



Manufactured to ISO9001



EN 14041:2004 (DOP 2017/Korlok/EN/01)
Notified body 0321
Floor Coverings (Internal)
ISO 10874 Class 23/33
Manufactured to EN 16511

