



	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	4,5 mm
Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee	Light industrial	10 years*
	Commercial	12 years *
	Residential	30 years *
Bevelled edge		No
Mass per unit area	EN ISO 23997	7470 g/m ²
Standards	EN 649/ EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874-light industrial	42: Light industrial general
	EN 685/EN ISO 10874- Commercial	33: Commercial heavy
	EN 685/EN ISO 10874- Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	≥7
Abrasion resistance	EN 649	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	≤ 0,10%
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 13 dB
Indentation - residual	EN 433/EN ISO 24343-1	Pass ≤ 0,1 mm
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0245 m ² K/W
		Suitable for underfloor heating. Max 27°C
**Slip resistance	DIN 51130	R10
	DIN 51097	See separate table
	EN 13893	DS
Adhesive		Most applications will not require the use of adhesives. However, we recommend the use of a tackifier for heavy traffic areas.
Recycling		Suitable
VOC emission	French VOC regulation (ISO 16000)	A+
Phthalate free		Yes

Slip Resistance

Product	Size (mm)	DIN 51097
LLP92	1050,0 X 250,0	B
LLP95	1050,0 X 250,0	B
LLP99	1050,0 X 250,0	B
LLP101	1050,0 X 250,0	B
LLP102	1050,0 X 250,0	B
LLP106	1050,0 X 250,0	B
LLP108	1050,0 X 250,0	B
LLP109	1050,0 X 250,0	B
LLP112	1050,0 X 250,0	B
LLP113	1050,0 X 250,0	B
LLP142	1050,0 X 250,0	B
LLP143	1050,0 X 250,0	B
LLP144	1050,0 X 250,0	B
LLP145	1050,0 X 250,0	B
LLP146	1050,0 X 250,0	B
LLP147	1050,0 X 250,0	B
LLP148	1050,0 X 250,0	B
LLP149	1050,0 X 250,0	B
LLP150	1050,0 X 250,0	B
LLP151	1050,0 X 250,0	B
LLT200	610,0 X 500,0	A
LLT201	610,0 X 500,0	A
LLT202	610,0 X 500,0	A
LLT203	610,0 X 500,0	A
LLT208	610,0 X 500,0	A
LLT209	610,0 X 500,0	A
LLT210	610,0 X 500,0	A
LLT211	610,0 X 500,0	A
LLT214	610,0 X 500,0	A
LLT215	610,0 X 500,0	A
LLT216	610,0 X 500,0	A
LLT217	610,0 X 500,0	A
LLT218	610,0 X 500,0	A
LLT219	610,0 X 500,0	A

*subject to terms see website

**Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132
 Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14
 Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204
 Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386
 e: info@designflooring.com
www.designflooring.com

Manufactured to ISO9001

