



	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2,5 mm
Wear layer	EN ISO 24340	0,55 mm
Guarantee	Light industrial	10 years *
	Commercial	12 years *
	Residential	30 years *
Bevelled edge	-	No
Mass per unit area	EN ISO 23997	4170 g/m ²
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874- Light industrial	42: Light industrial general
	EN 685/EN 10874- Commercial	33: Commercial heavy
	EN 685/EN 10874- Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	≥6
Abrasion resistance	EN 649	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/ EN ISO 23999	≤ 0,25%
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ EN ISO 24344	Pass ≤ 0,1 mm
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0120 m ² K/W Suitable for underfloor heating. Max 27°C
**Slip resistance	DIN 51130	R10 (except MLC01 = R9)
	DIN 51097	See separate table
	EN 13893	DS
Adhesive	Universal	Yes
	Acrylic	Yes
	Epoxy	Yes
	High Temperature	Yes
	Pressure sensitive	Yes
Recycling		Suitable
VOC emission	French VOC regulation (ISO 16000)	A+
	DIBt/AgBB	Pass
Phthalate free		Yes

Product	Size (mm)	Slip Resistance
		DIN 51097
MLC01	406,4 X 406,4	A
MLC07	406,4 X 406,4	B
MLC08	406,4 X 406,4	B
MS1	304,8 X 304,8	C
MS2	304,8 X 304,8	C
MS3	304,8 X 304,8	C
MS4	304,8 X 304,8	C
MS5	381,0 X 381,0	C
MX92	304,8 X 304,8	C
MX93	304,8 X 304,8	C
MX95	304,8 X 304,8	C
MX97	304,8 X 304,8	C
MX98	304,8 X 304,8	C

*subject to terms see website

**Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

For more information:

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132
 Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14
 Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204
 Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386
 e: info@designflooring.com
www.designflooring.com

Manufactured to ISO9001



EN 14041:2004 (DOP 2017/MA/EN/01)
Notified body 0321
Floor Coverings (Internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582

