

	Standard	Result	Product	Size (mm)
Size	EN ISO 24342	See separate table	KP103	914,4 X 152,4
Thickness	EN ISO 24346	2,0 mm	KP104	914,4 X 152,4
Wear layer	EN ISO 24340	0,3 mm	KP105	914,4 X 152,4
Surface treatment		K-Guard+ PU coating	KP131	914,4 X 152,4
Guarantee*	Light industrial	n/a	KP132	914,4 X 152,4
	Commercial	10 years	KP133	914,4 X 152,4
	Residential	30 years	KP134	914,4 X 152,4
Bevelled edge		No	KP135	914,4 X 152,4
Mass per unit area	EN ISO 23997	3605 g/m <sup>2</sup>	KP136	914,4 X 152,4
Standards	EN 649/EN ISO 10582	Heterogeneous PVC	KP137	914,4 X 152,4
Classification	EN 685/EN ISO 10874 - Light industrial	n/a	KP138	914,4 X 152,4
	EN 685/EN ISO 10874 - Commercial	31: Commercial moderate	KP139	914,4 X 152,4
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy	KP140	914,4 X 152,4
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1	KP32	914,4 X 101,6
Staining resistance	EN ISO 26987/EN 423	Excellent	KP39	914,4 X 101,6
Light fastness	EN ISO 105-B02	≥6	KP40	914,4 X 101,6
Abrasion resistance	EN 649	Group T	KP51	914,4 X 101,6
	EN ISO 10582	Type 1	KP94	914,4 X 152,4
Flexibility	EN ISO 24344	Pass	KP95	914,4 X 152,4
Dimensional stability	EN 434/EN ISO 23999	≤ 0,25%	KP96	914,4 X 152,4
Acoustic Impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 1 dB	KP97	914,4 X 152,4
Electrical behaviour body voltage	EN 1815	Pass	KP98	914,4 X 152,4
Indentation - residual	EN 433/EN ISO 24343-1	Pass ≤ 0,1 mm	KP99	914,4 X 152,4
Castor chair continuous use	EN 425/ISO 4918	Pass	PVP144	1219,2 x 177,8
Thermal resistance	ISO 8302	0,0084 m <sup>2</sup> K/W	PVP145	1219,2 x 177,8
		Suitable for underfloor heating. Max 27°C	PVP146	1219,2 x 177,8
Slip resistance**	DIN 51130	R10	PVP147	1219,2 x 177,8
	EN 13893	DS	PVP148	1219,2 x 177,8
Adhesive	Universal	Yes	PVP149	1219,2 x 177,8
	Acrylic	Yes	PVP150	1219,2 x 177,8
	Epoxy	Yes	SM-KP132	457,2 x 76,2
	High Temperature	Yes	SM-KP138	457,2 x 76,2
Recycling	Pressure sensitive	Yes	SM-KP95	457,2 x 76,2
		Suitable	SM-KP99	457,2 x 76,2
VOC emission	French VOC regulation (ISO 16000)	A+	ST10	304,8 X 304,8
Phthalate free	DIBt/AgBB	Pass	ST11	457,2 X 304,8
		Yes	ST12	457,2 X 304,8
			ST13	457,2 X 304,8
			ST14	457,2 X 304,8
			ST15	457,2 X 304,8
			ST16	457,2 X 304,8
			ST17	457,2 X 304,8
			ST5	304,8 X 304,8
			T98	304,8 X 304,8

\*Subject to terms see website

\*\*Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132

Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386

e: info@designflooring.com

[www.designflooring.com](http://www.designflooring.com)

